



A	Y	X	B	B2	I	D	Stack	Reach
Rahmenhöhe	Sitzwinkel	Lenkwinkel	OR direkt	OR waagrecht	1 1/8" Steuerrohr	Kettenstrebe		
420	74°	71°	535	545	145	450	536	402
460	73,5°	71°	550	560	180	450	572	403
500	73°	71,5°	565	575	200	450	588	404
540	72,5°	71,5°	580	590	215	450	602	409
580	72,5°	71°	590	600	230	450	614	410

M01 Komplettrad bzw. M1 Rahmen-Set (Rahmen, Gabel, Sattelklemme, Kleinteile). Robuster 26" Stahlrahmen (25Cr/Mo4 d.b.) für Alltag und Reise.

- phosphatiert, zweifach pulverbeschichtet (hochwertiges Polyester-Pulver) auch in ungepulvertem Zustand erhältlich
- Material: 25Cr/Mo4 d.b.
- Gewicht ohne Gabel RH 460: 2380 g (unlackiert)
- Gabel: Cr/Mo Ahead 1 1/8", gebogene Gabelscheiden mit durchgehenden Lowrider-Buchsen
- Gewindebuchsen M5 4x im Unterrohr
- Gewindebuchsen für Gepäckträger und Schutzblechmontage
- Gewindebuchsen für 3x Flaschenhalter
- Gewindebuchsen M6 2x in linker Kettenstrebe zur Befestigung von Pletscher Seitenständer
- Lichtkabelbohrung in Gabel und Unterrohr
- Bremszugführung durchgehend
- empfohlene Reifenbreite 42 bis 54 mm
- für Federgabel nicht geeignet

optional gegen Aufpreis:

- Hohlraumkonservierung Gabel&Rahmen
- Rahmen und Gabel im eigenes Design

M01 bike / M1 frame set (frame, fork, seat tube clamp, small parts) Solid 26" steel frame (25Cr/Mo4 d.b.) for daily use or trips.

- phosphated, double powder coated (high quality polyester powder), but also available without painting
- fork: Cr/Mo with lighting cable drilling, Ahead 1 1/8"
- 4x thread eyelets M5 in down tube
- rear carrier and mudguard mounts
- thread eyelets for 3 bottle holders
- 2x M6 thread eyelets in the left chain stay for Pletscher sidestand
- tire width 42 - 54 mm
- lighting cable drilling in fork and down tube
- persistent brake cable guiding
- weight excl. fork, size 460 mm: 2380 g (raw)
- not compatible with suspension forks

options for extra charge:

- cavity preservation
- frame and fork in own design